VOLTAGE BOOSTER CONVERTER

Field of the invention:

The invention relates to a voltage booster converter, or "boost converter", making it possible to obtain from a DC input voltage a DC output voltage of higher value than the supply voltage.

Background of the invention:

In order to power certain electronic devices, in particular those intended for aeronautics, it sometimes proves to be necessary to generate electric voltages of high level, from a low-voltage common supply generator. The "boost converters" used for this purpose are chopper converters that are nonisolated so as to retain high efficiencies and small dimensions.

Figure 1a shows a basic diagram of a voltage booster converter of the prior art.

The circuit of figure 1a is powered, via two input terminals A and B, by a generator E of DC input voltage Vin and provides a DC output voltage Vout on a load Rout in parallel with a capacitor Cout. The positive pole of the generator E is connected, across an inductor Lin and a diode Dd, to a terminal C of the resistor Rout in parallel with the capacitor Cout, the other terminal D of the resistor Rout being connected to the negative pole of the generator E. A switch Int connected, on the one hand, to the connection point of the inductor Lin and the diode Dd, and, on the other hand, to the negative pole of the generator E, periodically places the inductor Lin in parallel with the generator E.

The switch Int is turned on for the time Ton and open for the time Toff. The diode Dd is conducting for the time Toff and open for the time Ton. We refer to α=Ton/(Ton+Toff) as the duty ratio.

Figure 1b shows the control signal of the switch Int of the "boost converter".

When Int is closed, for the time Ton, the inductor Lin sees at its terminals the voltage Vin of the generator E. The current ILin in this inductor increases by the value:

$\Delta ILin_{Ton}$ = Vin.Ton/Lin

When the switch Int is open and the diode Dd conducts, that is to say for the time Toff, the inductor Lin sees at its terminals the difference between the input voltage Vin and the output voltage Vout. The current ILin in this inductor therefore decreases by the value:

$\Delta ILin_{Toff} = ((Vin-Vout).Toff)/Lin$

The equilibrium state is attained when the sum of these two variations is zero, i.e.:

$((Vin-Vout).Toff)/Lin + Vin.Ton/Lin = 0$

which leads to the expression for the equilibrium voltage:

$Vout = Vin/(1-\alpha)$

α lying between 0 and 1, the output voltage Vout is therefore higher than the input voltage Vin, the structure of figure 1a is that of a voltage booster.

Figure 1c shows the current in the "boost converter" of figure 1a.

In practice, the switch Int may advantageously be embodied by semiconductors. Mention may be made, in a nonlimiting manner, of MOS and bipolar transistors, IGBTs or MCTs.

The voltage booster converters of the prior art comprise limitations. Specifically, it is difficult to obtain voltage ratios Vout/Vin of greater than 5 while retaining optimal converter efficiency. Specifically, the switch is subjected at one and the same time to very large currents and high voltages.

Other nonisolated structures may be used. Mention may for example be made of the autotransformer type boost converter or the placing of two boost converters in series. Unfortunately, none of these solutions exhibits the expected efficiency performance.

Summary of the invention :

In order to alleviate the drawbacks of the voltage booster devices of the prior art, the invention proposes a voltage booster converter comprising:

- a pair of input terminals A and B for connecting a DC input voltage Vin between these two terminals;
- a pair P_0 of switches SB, SH in series connected by the switch SB to the input terminal B, the input terminal A being connected across an input inductor Lin to the connection point between the two switches SB and SH in

series, each switch SB, SH comprising control means so as to be placed simultaneously, one in an on state the other in an isolated state;

- a pair of output terminals C and D, for powering, by an output voltage Vout, a load Rout, the output terminal D being connected to the input terminal B, comprising:

- K other additional pairs P_1, P_2,....P_i,...P_{K-1}, P_K of switches in series with the pair P_0 between the output terminal C and the switch SH with i = 1, 2,...K-1, K, the two switches of one and the same additional pair P_i being connected across an energy recovery inductor Lr_i;

- K input groups, Gin_1, Gin_2,...Gin_i,...Gin_{K-1}, Gin_K, of Ni capacitors C of like value each in series, with i= 1, 2,...K-1, K and Ni = i, the electrode of the capacitors of one of the two ends of each input group being connected to the common point between the two switches SB, SH of the pair P_0, at least the electrode of the capacitors of each of the other ends of the input groups being connected respectively to the common point between each the switch SH_i and the recovery inductor Lr_i of the corresponding pair P_i of like rank i,

- K output groups, $Gout_1$, $Gout_2$,...$Gout_i$,...$Gout_{K-1}$, $Gout_K$, of Mi capacitors C of like value each in series, with i = 1, 2,...K and Mi=(K+1)–i, the electrode of the capacitors of one of the two ends of the output groups being connected to the output terminal C, at least the electrode of the capacitors of each of the other ends of the output groups being connected respectively to the connection point between two pairs of consecutive switches P_{i-1} and P_i;

in that the switches of these other K additional pairs are controlled so as to form, when the switch SB of the pair P_0 linked to the terminal B is switched to the on state for a time Ton, a first capacitor network connected on the one hand across the switch SB to the terminal B and, on the other hand, to the terminal C, comprising the groups of input capacitors in series with the groups of the output capacitors such that a group of input capacitors Gin_i is in series with its respective group of output capacitors $Gout_i$,

and in that when the switch SB of the pair P_0 linked to the input terminal B is switched to the isolated state for a time Toff these other K pairs of switches form a second capacitor network connected to the terminal A across the input inductor Lin comprising the input group Gin_K in parallel with the output group $Gout_1$, in parallel with groups of input capacitors in series

with groups of the output capacitors such that a group of input capacitors Gin_{i-1} is situated in series with a group of output capacitors $Gout_i$.

The voltage Vout at the output of the converter is dependent on the duty ratio α=Ton/(Ton+Toff), the capacitors C of the networks having one and the same value, the voltage Vout is given by the relation:

$$Vout = (Vin/(1-\alpha)).(K+1).$$

The switches comprise a control input (control means) so as to be placed simultaneously, one in an on state through the application to its control input of a first control signal, the other in an isolated state by the application to its control input of a second control signal complementary to the first.

In practice, the switches may advantageously be embodied by semiconductors. Mention may be made, in a nonlimiting manner, of MOS and bipolar transistors, IGBTs or MCTs.

The converter furthermore comprises an output filtering capacitor Cout in parallel with the load Rout between the output terminals C and D.

In an embodiment of a booster converter, according to the invention, providing a positive output voltage Vout, the potential of the terminal A is greater than the potential of the terminal B, the potential of the output terminal C is greater than the potential of the output terminal D.

In another embodiment of a voltage booster converter, according to the invention, providing a negative voltage, the potential of the terminal A is less than the potential of the terminal B, the potential of the output terminal C is then less than the potential of the output terminal D.

Brief description of drawings :

The invention will be better understood with the aid of exemplary embodiments according to the invention, with reference to the indexed drawings, in which:

- figure 1a, already described, shows a basic diagram of a voltage booster converter according to the prior art;
- figure 1b shows the control signal of the switch Int of the "boost converter" of figure 1a;
- figure 1c shows the current in the "boost converter" of figure 1a;

- figure 2 shows the general structure of the converter according to the invention comprising K pairs of additional switches;

- figure 3a represents an exemplary embodiment of a voltage booster converter with two stages, according to the invention, without the recovery inductor;

- figure 3b shows the structure of a negative version of the converter of figure 3a;

- figure 4a shows a simplified structure of the voltage booster converter of figure 3a;

- figure 4b shows the structure of a negative version of the converter of figure 4a;

- figure 5a shows the voltage booster converter of figure 3a comprising an energy recovery inductor;

- figure 5b shows a first version of an impedance Z_i for enhancing the reliability of the converter according to the invention;

- figure 5c shows another impedance Z_i for enhancing the reliability of the converter according to the invention;

- figure 5d shows a simplified version of the voltage booster converter of figure 5a;

- figure 6 shows an equivalent diagram of the converter of figure 5a according to the invention during the time Ton;

- figure 6a shows an equivalent diagram of the converter of figure 5d according to the invention during the time Ton;

- figure 7 shows the control signals of the switches SB and SB1 of the converter of figure 5a;

- figure 7a shows the control signals of the switches SB of the converter of figure 5d;

- figure 8 shows the variation of the current in the energy recovery inductor of the converter of figure 5a;

- figure 8a shows the variation of the current in the energy recovery inductor of the converter of figure 5d;

- figure 9 represents the energy space of the recovery inductor Lr_1 and of the capacitor Ceq of figure 6;

- figure 10a represents a first practical structure of the converter according to the invention not comprising any interconnections between the capacitors of one and the same level of potential;

- figure 10b represents the negative version of the converter of figure 10a;

- figure 11 represents another practical structure comprising interconnections between the capacitors of one and the same level of potential;

- figure 12 represents the negative version of the converter of figure 11.

Detailed description of embodiments :

Figure 2 shows the general structure of the voltage booster converter according to the invention comprising K pairs of additional switches. The converter of figure 2 comprises, furthermore, an output filtering capacitor Cout in parallel with the load Rout between the output terminals C and D.

In the general structure of the "boost converter" of figure 2 according to the invention the voltages Vc across the terminals of the capacitors of the input groups Gin_i or of the output groups $Gout_i$ have one and the same DC value, thus, the capacitors situated at one and the same level of potential may be linked together. It is thus possible simply to produce various structures of the voltage booster converter that we shall see subsequently.

Figure 3a represents an exemplary embodiment of a voltage booster converter with two stages (a single additional pair), according to the invention, without the recovery inductor, comprising two pairs of switches P_0 and P_1, each having two switches connected in series. The switches SB, SH for the pair P_0 and the switches SB_1, SH_1 for the additional pair P_1. Each switch of a pair comprises a control input so as to be placed simultaneously, the one in an on state by the application to its control input of a first control signal C1, the other in an isolated state by the application to its control input of a second control signal C2 complementary to the first.

Figure 3b represents the negative voltage version of the voltage booster converter with two stages of figure 3a. The converter of figure 3b, of the same structure as that of figure 3a, is powered by a generator E providing

a negative potential Vin between the input terminals A and B. The polarity of the output capacitor Cout is then inverted.

Figure 4a shows a simplified structure of the booster converter of figure 3a comprising two pairs of switches. In this simplified structure, the switches SB_1, SH_1 of the pair P_1 are replaced by diodes DB_1, DH_1. The switch SH of the pair P_0 connected to the pair P_1 is also replaced by a diode DH, only the switch SB of the pair P_0 must be retained. The cathode of a diode of a pair (P_0) is connected to the anode of the diode of the next pair (P_1).

Figure 4b shows the simplified structure of the negative version of the booster converter of figure 3b. In this structure of figure 4b, the "mirror" of the structure of figure 4a, the anode of the diode of a pair (P_0) is connected to the cathode of the diode of the next pair (P_1). Just as for the negative voltage version of the converter of figure 3b the polarity of the output capacitor Cout is inverted.

Figure 5a shows the voltage booster converter of figure 3a comprising an energy recovery inductor Lr_1 allowing an improvement of the efficiency of the converter. The input capacitor is designated by Ce and the output capacitor by Cs.

We shall, subsequently, explain the manner of operation of the voltage booster converter of figure 5a according to the invention.

Figure 6 shows an equivalent diagram of the converter of figure 5a according to the invention comprising the recovery inductor Lr_1, during the period Ton corresponding to the period of conduction of the switches of the two pairs SB and SB_1. During this time Ton the switches SB and SB_1 are closed, the switches SH and SH_1 are open, the output capacitor Cout is in parallel with the two capacitors Ce and Cs in series with the recovery inductor Lr_1.

The recovery inductor Lr_1 is sized so as to obtain a resonance of the oscillating circuit of figure 6 such that:

$$Ton \geq \pi \sqrt{Lr_1 \cdot Ceq}$$

with

$$Ceq = \frac{1}{\frac{1}{Cout} + \frac{1}{Ce} + \frac{1}{Cs}}$$

For an optimal result, Ton is constant and equal to around half the period of the resonant frequency of the equivalent circuit of figure 6.

Figure 6a shows an equivalent diagram of the converter of figure 5d according to the invention during the time Ton.

In the case of figure 6a, the diode DB1 automatically opens the resonant circuit upon the zeroing of the current in the inductor Lr_1. In this case, it suffices for the following relation to be satisfied:

$$Ton \geq \pi \sqrt{Lr_1 \cdot Ceq}$$

Figure 7 shows the control signals of the switches SB and SB1 of the converter of figure 5a. The other switches are controlled in a complementary manner.

Figure 8 shows the variation of the current ILr_1 in the energy recovery inductor Lr_1 as well as the sum of the voltages (Vce +Vcs) across the terminals of the respective input Ce and output Cs capacitors (converter of figure 5a).

At the time t1 when toggling from Toff to Ton, the current in the inductor is zero, the voltage (Vce + Vcs) across the terminals of the capacitors Ce and Cs is lower than the mean value of Vout and increases, passing through the mean value of Vout, the current in the inductor Lr_1 increases while storing up magnetic energy, passes through a maximum value when (Vce + Vcs) passes through the mean of Vout, then the current decreases down to a zero value, corresponding to the end of Ton, yielding the energy to the capacitors Ce and Cs. During Toff, the current in the inductor Lr1 remains zero, the sum of the voltages (Vce+Vcs) decreases since Ce and Cs are traversed by the current of the inductor Lin, then the cycle recommences at the start of Ton.

Figure 7a shows the control signals of the switches SB of the converter of figure 5d. Figure 8a shows the variation of the current in the energy recovery inductor of the converter of figure 5d.

Figure 9 represents the energy space of the recovery inductor Lr_1 and of the capacitor Ceq of the converter. The abscissa axis represents the capacitive energy Wc, the ordinate axis the inductive energy WLr_1, the energy variation between the inductor and the capacitors occurring in the time Ton. The energy is transferred from the capacitors to the recovery inductor then yielded to the capacitors.

The tuning of the circuit of the converter to the operating frequency with the recovery inductor Lr_1 considerably reduces the losses of rebalancing of charges in the capacitors Ce and Cs in the circuit of the "boost converter" according to the invention. These losses then become practically zero. This improvement of the converter of figure 3a with recovery inductors is applicable in the general case to K additional pairs of switches (see figure 2).

Furthermore, in order to make the booster converter according to the invention more reliable, the converter represented in figure 5d comprises in parallel with the recovery inductor Lr_1 in series with the switch SH_1 of the pair P_1 an impedance Z_1.

Specifically, in practice, Ton does not represent perfectly half the resonant period of the equivalent circuit of figure 6, the impedance Z_1 makes it possible to dissipate the residual current and protect the switches which are generally MOS transistors.

This improvement of the converter of figure 5a is applicable in the general case, thus each additional pair P_i of the converter according to the invention comprises in parallel with the recovery inductor Lr_i in series with the switch SH_i of the pair P_i an impedance Z_i.

Figure 5b shows a first version of the impedance Z_i for enhancing the reliability of the converter according to the invention. The impedance Z_i comprises a diode Ddz in series with a resistor r, the anode of the diode Ddz being linked, in the circuit of the converter, to the recovery inductor and in a second version, shown in figure 5c, another impedance Z_i comprises the diode Ddz in series with a Zener diode Dz, the two cathodes of the diode Dd and the Zener diode Dz being linked together, the anode of the diode Ddz being linked, in the circuit of the converter, to the recovery inductor.

Other types of impedance Z_i for dissipating the residual energy of the inductor Lr_i may of course be used, for example RC or RCD cells used conventionally in the field of power electronics.

Figure 5d shows a simplified version of the voltage booster converter of figure 5a comprising two pairs of switches P_0 and P_1 and a recovery inductor Lr_1. In this simplified structure, the switches SB_1 and SH_1 of the pair P_1 are replaced by diodes DB_1 and DH_1. The switch SH of the pair P_0 connected to the pair P_1 is also replaced by a diode DH, only the switch SB of the pair P_0 has to be retained, the cathode of a diode of a pair being

connected to the anode of the diode of the next pair. As in the booster converter of figure 5a using switches, the two diodes of the pair P_1 are linked in series across a recovery inductor Lr_1.

The embodiment of the simplified voltage booster converter with diodes remains valid for any number of additional pairs, thus, in the general case, the switches SB_i and SH_i of the additional pairs P_i are replaced respectively by diodes DB_i and DH_i. The switch SH of the pair P_0 connected to the pair P_1 is a diode DH, only the switch SB of the pair P_0 has to be retained. The cathode of a diode of a pair P_{i-1} being connected to the anode of the diode of the next pair P_i. As in the booster converter with switches of figure 5a, the two diodes of the pair P_i are linked in series across a recovery inductor Lr_1.

The explanation of the manner of operation of the series converter comprising the recovery inductor Lr_1 with two pairs (K=1) remains valid for any number of K additional pairs. Specifically, the currents in the various pairs P_i and in the corresponding recovery inductor Lr_i are the same, the number of elementary capacitors C in the groups placed in series by the switches being the same.

The voltage booster converter general structure represented in figure 2 makes it possible to simply embody various other practical structures and to determine directly the value of the capacitors in each input or output branch.

Specifically, as was stated previously, in the general structure of figure 2 comprising capacitors C of like value, the voltages Vc across the terminals of each of the capacitors are the same for the input groups and the same for the output groups, therefore, the capacitors of one and the same level of potential may be connected in part or in whole in parallel.

The capacitors of one and the same potential level Nin_1 are, for example, all those of the input groups Gin_1, Gin_2,...Gin_i,...Gin_{K-1}, Gin_K having an electrode connected to the common point between the two switches of the pair P_0, of a potential level Nin_2, all those connected by an electrode to the free electrodes of the capacitors of the level Nin_1 and by the other electrode to those of the next level Nin_3 and so on and so forth up to the level Nin_K.

Likewise, for the capacitors of the output groups, we shall have the level $Nout_1$ for all those of the output groups $Gout_1$, $Gout_2$,...$Gout_i$,...$Gout_{K-1}$,

$Gout_K$ having an electrode connected to the common point between the two pairs of switches P_0 and P_1, of a potential level $Nout_2$ all those connected by an electrode to the free electrodes of the capacitors of the level $Nout_1$ and by the other electrode to those of the next level $Nout_3$ and so on and so forth up to the level $Nout_K$.

The dotted lines in the diagram of figure 2 represent the possible connections between the capacitors C of like value.

Figure 10a represents a first practical structure of the converter according to the invention not comprising any interconnections between the capacitors of one and the same level of potential, each of the input Gin_i or output $Gout_i$ groups respectively comprises a single capacitor Cea_1, Cea_2,....Cea_i.....Cea_K, for the input groups Gin_i and Csa_1, Csa_2...Csa_i... Csa_K, for the output groups $Gout_i$.

The value of each of the input capacitors Cea_i is deduced simply from the general structure by calculating the resultant capacitance of the Ni=i capacitors C in series, with i=1, 2,....K, i being the order of the input group considered:

$Cea_1 = C$ i=1
$Cea_2 = C/2$ i=2
....
$Cea_i = C/i$ i
.....
$Cea_K = C/K$ i=K

The value of each of these output capacitors Csa_i is deduced simply from the general structure by calculating the resultant capacitance of Mi=(K+1)- i capacitors C in series, i being the order of the output group considered:

$Csa_1 = C/K$ i=1
$Csa_2 = C/(K-1)$ i=2
....
$Csa_i = C/(K+1)-i$ i
.....

$Csa_K = C$ i=K

Figure 10b represents the first practical structure of the converter of figure 10a in a negative version not comprising any interconnections between the capacitors of one and the same level of potential.

Figure 11 represents another practical structure of the converter according to the invention, in a positive version, comprising interconnections between the capacitors of one and the same level Nv of potential (capacitors in parallel), the structure comprises a single input group Gin and a single output group Gout. The input capacitor Ceb_i, for each of the potential levels Nin_i, connected between the connection points of the switches of two consecutive pairs P_i, P_{i-1}, will be deduced simply by calculating the capacitor Ceb_i equivalent to the capacitors in parallel of the level Nin_i, of potential considered, i.e.:

$Ceb_1 = C.K$ i=1
$Ceb_2 = C.(K-1)$ i=2
....
$Ceb_i = C.((K+1)-i)$ i
.....
$Ceb_K=C$ i=K

The output capacitor Csb_i of each of the levels of potential $Nout_i$, connected in parallel with its respective pair of switches P_i will be deduced simply by calculating the capacitor Csb_i equivalent to the capacitors in parallel of the level $Nout_i$ considered, i being the order of the output level of potential considered, i.e.:

$Csb_1 = C$ i=1
$Csb_2 =C.2$ i=2
....
$Csb_i = C.((K+1)-i)$ i
.....
$Csb_K =C.K$ i=K

Figure 12 represents the voltage booster converter of figure 11, in a simplified negative voltage version, comprising interconnections between the capacitors of one and the same potential level Nv. In this simplified version, the switches SB_i and SH_i of the additional pairs P_i are replaced respectively by diodes DB_i and DH_i. The switch SH of the pair P_0 connected to the pair P_1 is a diode DH, only the switch SB of the pair P_0 has to be retained. The anode of a diode of a pair P_{i-1} being connected to the cathode of the diode of the next pair P_i. The converter of figure 12, of the same structure as that of figure 11, is powered by a generator E providing a negative potential Vin between the input terminals A and B. The voltage Vout being negative, the polarity of the output capacitor Cout is then inverted.

In other embodiments it is of course possible to combine the two types of practical embodiments by placing capacitors in parallel for certain groups and in series for others.

It is also possible to embody conversion structures by combining several converters in parallel, be they positive and/or negative. The control signals of the converters of the conversion structure may then advantageously be out of phase so as to reduce the input and/or output current ripples of the booster converters.

The booster converter according to the invention makes it possible to obtain greater efficiencies than the voltage booster converters of the prior art with voltage ratios Vout/Vin of appreciably greater than five.

VOLTAGE BOOSTER CONVERTER

Voltage booster converter comprising a pair of input terminals A and B for connecting a DC input voltage Vin between these two terminals; a pair P_0 of switches SB, SH in series connected by the switch SB to the input terminal B, the input terminal A being connected across an input inductor Lin to the connection point between the two switches SB and SH in series, each switch SB, SH comprising a control input so as to be placed simultaneously, one in an on state the other in an isolated state; a pair of output terminals C and D, for powering, by an output voltage Vout, a load Rout, the output terminal D being connected to the input terminal B; K other additional pairs P_1, P_2,....P_i,...P_{K-1}, P_K of switches in series between the output terminal C and the free side of the switch SH with i = 1, 2,...K-1, K, the two switches of one and the same additional pair P_i being connected across an energy recovery inductor Lr_1; K input groups, Gin_1, Gin_2,...Gin_i,...Gin_{K-1}, Gin_K, of Ni capacitors C of like value each in series, with i= 1, 2,...K-1, K and Ni = i; K output groups, $Gout_1$, $Gout_2$,...$Gout_i$,...$Gout_{K-1}$, $Gout_K$, of Mi capacitors C of like value each in series, with i= 1, 2,...K and Mi=(K+1)–i. The switches of these other K additional pairs are controlled simultaneously by the first and second complementary control signals.